

Material Safety Data Sheet

Print Date: 01/11/2006

Revision Date : 01/11/2006

Version : 1.0

Trade name: **ATE Cylinder Paste**

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : ATE Cylinder Paste
MSDS Number : 88810003551
Product Use Description : technical preservative and anti-corrosion agent
Company : **Continental Teves AG & Co. oHG**
Guerickestr. 7
60488 Frankfurt a. M.
Germany
Telephone : + 49 69 76 03 1
Telefax : + 49 69 76 10 61
Contact person : Central Environment & Safety , Central Laboratory
Emergency telephone number : + 49 61 32 84 46 3

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Regulatory status : This product, material or substance is a WHMIS controlled product per Sections 33 - 66, Part IV of the CPR.

Signal Word : WARNING
Form : paste
Odour : characteristic
Odour - Control parameters : no data available
Hazard Summary : Irritant

Potential Health Effects

Eyes : Causes eye irritation.
Skin : May cause skin irritation.
Target Organs : Eyes
Skin

Carcinogenicity:

NTP : No component of this product present at levels greater than or equal to 0.1 % is identified as a known or anticipated carcinogen by NTP.

Material Safety Data Sheet

Print Date: 01/11/2006

Revision Date : 01/11/2006

Version : 1.0

Trade name: **ATE Cylinder Paste**

-
- | | |
|------------|--|
| IARC | : No component of this product present at levels greater than or equal to 0.1 % is identified as probable, possible or confirmed human carcinogen by IARC. |
| OSHA | : No component of this product present at levels greater than or equal to 0.1 % is identified as a carcinogen or potential carcinogen by OSHA. |
| CA Prop 65 | : This product does not contain any chemicals known to State of California to cause cancer, birth, or any other reproductive defects. |
-

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No.	Weight %
2,4,6-tri-sec-Butylphenol	5892-47-7	>= 5 - < 10
2,2'-(Octylimino)bisethanol	15520-05-5	>= 1 - < 5

SECTION 4. FIRST AID MEASURES

- | | |
|----------------|--|
| General advice | : Never give anything by mouth to an unconscious person. In the case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Remove from exposure, lie down. |
| Inhalation | : Move to fresh air in case of accidental inhalation of vapours or decomposition products. Keep patient warm and at rest. If symptoms persist, call a physician. |
| Skin contact | : Wash off with soap and water. |
| Eye contact | : In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. |
| Ingestion | : If swallowed, seek medical advice immediately and show this container or label. If a person vomits when lying on his back, place him in the recovery position. |
-

SECTION 5. FIRE-FIGHTING MEASURES

- | | |
|-------------|---|
| Form | : paste |
| Flash point | : > 145 °C (> 293 °F)
Method: ISO 2719 |
-

Material Safety Data Sheet

Print Date: 01/11/2006

Revision Date : 01/11/2006

Version : 1.0

Trade name: **ATE Cylinder Paste**

Ignition temperature	:	> 300 °C (> 572 °F)
Lower explosion limit	:	Note: not applicable
Upper explosion limit	:	Note: not applicable
Suitable extinguishing media	:	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Extinguishing media which must not be used for safety reasons	:	high volume water jet
Specific hazards during fire fighting	:	Fire will produce dense black smoke containing hazardous combustion products (see heading 10).
Special protective equipment for fire-fighters	:	Use personal protective equipment. Wear self-contained breathing apparatus and protective suit. complete suit protecting against chemicals
Further information	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Standard procedure for chemical fires.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions	:	Refer to protective measures listed in sections 7 and 8. Ventilate the area. Avoid contact with skin, eyes and clothing. Avoid inhalation of vapour or mist.
Environmental precautions	:	Do not flush into surface water or sanitary sewer system.
Methods for cleaning up	:	Wipe up with absorbent material (e.g. cloth, fleece).

SECTION 7. HANDLING AND STORAGE

Handling

Handling	:	For personal protection see section 8.
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.

Material Safety Data Sheet

Print Date: 01/11/2006

Revision Date : 01/11/2006

Version : 1.0

Trade name: **ATE Cylinder Paste**

Dust explosion class : not applicable

Storage

Requirements for storage areas and containers : Store in original container.
Keep containers tightly closed in a dry, cool and well-ventilated place.

Advice on common storage : Never allow product to get in contact with water during storage.
Keep away from food, drink and animal feeding stuffs.
Keep away from oxidising agents, strongly acid or alkaline materials and amines.

Storage temperature : 5 - 30 °C (41 - 86 °F)

Other data : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Contains no substances with occupational exposure limit values.

Engineering measures : Provide adequate ventilation.

Eye protection : In case of splash hazard, wear protective goggles.

Hand protection : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work.
For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer.

Respiratory protection : In case of insufficient ventilation wear suitable respiratory equipment.
respirator with A filter
Respirator with a vapour filter (EN 141)

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
Please thoroughly clean and care for the skin after finishing

Material Safety Data Sheet

Print Date: 01/11/2006

Revision Date : 01/11/2006

Version : 1.0

Trade name: **ATE Cylinder Paste**

work.
Wash contaminated clothing before re-use.
When using, do not eat, drink or smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Form	: paste
Odour	: characteristic
Flash point	: > 145 °C (> 293 °F) Method: ISO 2719
Ignition temperature	: > 300 °C (> 572 °F)
Lower explosion limit	: not applicable
Upper explosion limit	: not applicable
pH	: 8 - 9 at 20 °C (68 °F)
Boiling point/range	: > 300 °C (> 572 °F) at 1,013 mbar
Vapour pressure	: < 0.1 mbar at 20 °C (68 °F)
Relative vapour density	: not applicable
Density	: 1 g/cm ³ at 20 °C (68 °F) Method: DIN 51757
Bulk density	: not applicable
Water solubility	: at 20 °C (68 °F) insoluble
Partition coefficient (n-octanol/water)	: not applicable
Viscosity, kinematic	: 600 - 800 mm ² /s at 20 °C (68 °F)

Material Safety Data Sheet

Print Date: 01/11/2006

Revision Date : 01/11/2006

Version : 1.0

Trade name: **ATE Cylinder Paste**

VOC : 0.39 %

SECTION 10. STABILITY AND REACTIVITY

Conditions to avoid : no data available

Materials to avoid : strong acids and oxidizing agents

Hazardous decomposition products : Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke.

Hazardous reactions : Note: No decomposition if used as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute oral toxicity : LD50 rat
Dose: > 7,105 mg/kg
Effects due to ingestion may include:
vomiting

Eye irritation : no data available

Carcinogenicity : No data is available on the product itself.

Toxicity to reproduction : No data is available on the product itself.

Teratogenicity : No data is available on the product itself.

SECTION 12. ECOLOGICAL INFORMATION

Biodegradability : 63 %

Physico-chemical removability : > 70 %
readily eliminated

Bioaccumulation : no data available

Toxicity to fish : LC50
Species: Brachydanio rerio (zebra fish)
Dose: > 100 mg/l
Exposure time: 96 h

Material Safety Data Sheet

Print Date: 01/11/2006

Revision Date : 01/11/2006

Version : 1.0

Trade name: **ATE Cylinder Paste**

Adsorbed organic bound halogens (AOX) : not included
Volatile organic compounds (VOC) content : 0.39 %

Additional ecological information : Contains no substances known to be hazardous to the environment or not degradable in waste water treatment plants.

SECTION 13. DISPOSAL CONSIDERATIONS

Adequate disposal : In accordance with local and national regulations.

SECTION 14. TRANSPORT INFORMATION

DOT 49 CFR

Not dangerous goods

TDGR

Not dangerous goods

ICAO / IATA-DGR

Not dangerous goods

IMDG-Code

Not dangerous goods

SECTION 15. REGULATORY INFORMATION

TSCA Status : Not On TSCA Inventory

Diglycerol propoxylated 61710-63-2

DSL Status : This product contains the following components that are not on the Canadian DSL nor NDSL lists.

Diglycerol propoxylated 61710-63-2

Material Safety Data Sheet

Print Date: 01/11/2006

Revision Date : 01/11/2006

Version : 1.0

Trade name: **ATE Cylinder Paste**

California Prop. 65 : This product does not contain any chemicals known to State of California to cause cancer, birth, or any other reproductive defects.

WHMIS Classification : D2B Toxic Material Causing Other Toxic Effects
Moderate skin irritant
Severe eye irritant

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

SECTION 16. OTHER INFORMATION

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Prepared by : GWU mbH
Birlenbacher Str. 18
D-57078 Siegen
Germany
Telephone: +49-(0)271-88072-0
Revision Date : 01/11/2006