

## Material Safety Data Sheet

Print Date: 02/16/2006

Revision Date : 02/16/2006

Version : 2.0

Trade name: **Original ATE Brake Fluid TYP 200; 10m (DOT4)**

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Original ATE Brake Fluid TYP 200; 10m (DOT4)  
MSDS Number : 888100003547  
Product Use Description : Hydraulic fluid  
Company : **Continental Teves AG & Co. oHG**  
**Guerickestr. 7**  
**60488 Frankfurt a. M.**  
**Germany**  
Telephone : + 49 69 76 03 1  
Telefax : + 49 69 76 10 61  
Contact person : Central Environment & Safety , Central Laboratory  
Emergency telephone number : + 49 61 32 84 46 3

### SECTION 2. HAZARDS IDENTIFICATION

#### Emergency Overview

**Regulatory status** : This product, material or substance is a WHMIS controlled product per Sections 33 - 66, Part IV of the CPR.

Signal Word : WARNING  
Form : liquid  
Odour : characteristic  
Odour - Control parameters : no data available  
Hazard Summary : Irritant

#### Potential Health Effects

Eyes : Causes eye irritation.  
Skin : May cause skin irritation.  
Target Organs : Eyes  
Skin

Carcinogenicity:

NTP : No component of this product which is present at levels greater than or equal to 0.1 % is identified as a known or anticipated carcinogen by NTP.

## Material Safety Data Sheet

Print Date: 02/16/2006

Revision Date : 02/16/2006

Version : 2.0

Trade name: **Original ATE Brake Fluid TYP 200; 10m (DOT4)**

- 
- |            |   |
|------------|---|
| IARC       | : No component of this product which is present at levels greater than or equal to 0.1 % is identified as probable, possible or confirmed human carcinogen by IARC. |
| OSHA       | : No component of this product which is present at levels greater than or equal to 0.1 % is identified as a carcinogen or potential carcinogen by OSHA.             |
| CA Prop 65 | : This product does not contain any chemicals known to State of California to cause cancer, birth defects or any other reproductive harm.                           |
- 

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No.	Weight %
2-(2-(2-Methoxyethoxy)ethoxy)ethanol	112-35-6	>= 5 - < 10
2,2'-(Octylimino)bisethanol	15520-05-5	>= 1 - < 5

---

### SECTION 4. FIRST AID MEASURES

- |                |  |
|----------------|--|
| General advice | : Never give anything by mouth to an unconscious person. In the case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Remove from exposure, lie down. |
| Inhalation     | : Move to fresh air in case of accidental inhalation of vapours or decomposition products. Keep patient warm and at rest. If symptoms persist, call a physician.   |
| Skin contact   | : Wash off with soap and water.  |
| Eye contact    | : In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  |
| Ingestion      | : If swallowed, seek medical advice immediately and show this container or label. If a person vomits when lying on his back, place him in the recovery position.   |
- 

### SECTION 5. FIRE-FIGHTING MEASURES

- |             |   |
|-------------|---|
| Form        | : liquid                                  |
| Flash point | : > 130 °C (> 266 °F)<br>Method: ISO 2592 |
-

## Material Safety Data Sheet

Print Date: 02/16/2006

Revision Date : 02/16/2006

Version : 2.0

Trade name: **Original ATE Brake Fluid TYP 200; 10m (DOT4)**

---

Ignition temperature	:	> 200 °C (> 392 °F) Method: DIN 51794
Lower explosion limit	:	Note: not determined
Upper explosion limit	:	Note: not determined
Suitable extinguishing media	:	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Extinguishing media which must not be used for safety reasons	:	high volume water jet
Specific hazards during fire fighting	:	Fire will produce dense black smoke containing hazardous combustion products (see heading 10).
Special protective equipment for fire-fighters	:	Use personal protective equipment. Wear self-contained breathing apparatus and protective suit. complete suit protecting against chemicals
Further information	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Standard procedure for chemical fires.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions	:	Refer to protective measures listed in sections 7 and 8. Ventilate the area. Avoid contact with skin, eyes and clothing. Avoid inhalation of vapour or mist.
Environmental precautions	:	Do not flush into surface water or sanitary sewer system.
Methods for cleaning up	:	Wipe up with absorbent material (e.g. cloth, fleece).

---

### SECTION 7. HANDLING AND STORAGE

#### Handling

Handling	:	For personal protection see section 8.
Advice on protection	:	Normal measures for preventive fire protection.

---

## Material Safety Data Sheet

Print Date: 02/16/2006

Revision Date : 02/16/2006

Version : 2.0

Trade name: **Original ATE Brake Fluid TYP 200; 10m (DOT4)**

against fire and explosion  
 Dust explosion class : not applicable

### Storage

Requirements for storage areas and containers : Store in original container.  
 Keep containers tightly closed in a dry, cool and well-ventilated place.

Advice on common storage : Never allow product to get in contact with water during storage.  
 Keep away from food, drink and animal feeding stuffs.  
 Keep away from oxidising agents, strongly acid or alkaline materials and amines.

Storage temperature : 5 - 30 °C (41 - 86 °F)

Other data : No decomposition if stored and applied as directed.

## SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Exposure Guidelines

Contains no substances with occupational exposure limit values.

Engineering measures : Provide adequate ventilation.

Eye protection : In case of splash hazard, wear protective goggles.

Hand protection : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work.  
 For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer.

Respiratory protection : In case of insufficient ventilation wear suitable respiratory equipment.  
 respirator with A filter  
 Respirator with a vapour filter (EN 141)

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.

## Material Safety Data Sheet

Print Date: 02/16/2006

Revision Date : 02/16/2006

Version : 2.0

Trade name: **Original ATE Brake Fluid TYP 200; 10m (DOT4)**

Please thoroughly clean and care for the skin after finishing work.  
Wash contaminated clothing before re-use.  
When using, do not eat, drink or smoke.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Form	: liquid
Odour	: characteristic
Flash point	: > 130 °C (> 266 °F) Method: ISO 2592
Ignition temperature	: > 200 °C (> 392 °F) Method: DIN 51794
Thermal decomposition	: > 360 °C (> 680 °F)
Lower explosion limit	: not determined
Upper explosion limit	: not determined
pH	: 7 - 8 at 20 °C (68 °F)
Boiling point/range	: > 280 °C (> 536 °F) at 1,013 mbar
Vapour pressure	: < 0.1 mbar at 20 °C (68 °F)
Density	: 1.07 - 1.09 g/cm <sup>3</sup> at 20 °C (68 °F) Method: DIN 51757
Bulk density	: not applicable
Water solubility	: 350 g/l at 20 °C (68 °F)
Partition coefficient (n-octanol/water)	: no data available
Viscosity, kinematic	: 17 - 18 mm <sup>2</sup> /s at 20 °C (68 °F)

## Material Safety Data Sheet

Print Date: 02/16/2006

Revision Date : 02/16/2006

Version : 2.0

Trade name: **Original ATE Brake Fluid TYP 200; 10m (DOT4)**

VOC : 5 %

### SECTION 10. STABILITY AND REACTIVITY

Conditions to avoid : no data available

Materials to avoid : strong acids and oxidizing agents

Hazardous decomposition products : Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), dense black smoke.

Thermal decomposition : > 360 °C

Hazardous reactions : Note: No decomposition if used as directed.

### SECTION 11. TOXICOLOGICAL INFORMATION

Acute oral toxicity : no data available

Acute dermal toxicity : no data available

Acute inhalation toxicity : no data available

Skin irritation : no data available

Eye irritation : no data available

Sensitization : no data available

Carcinogenicity : No data is available on the product itself.

Toxicity to reproduction : No data is available on the product itself.

Teratogenicity : No data is available on the product itself.

**Component:**

2-(2-(2-Methoxyethoxy)ethoxy)ethanol

112-35-6

Acute oral toxicity: LD50 rat  
Dose: 11,850 mg/kg

Acute dermal toxicity: LD50 rabbit  
Dose: 7,448 mg/kg

Skin irritation: Classification: Irritating to skin.  
Result: Mild skin irritation

Eye irritation: Classification: Irritating to eyes.  
Result: Mild eye irritation

## Material Safety Data Sheet

Print Date: 02/16/2006

Revision Date : 02/16/2006

Version : 2.0

Trade name: **Original ATE Brake Fluid TYP 200; 10m (DOT4)**

### SECTION 12. ECOLOGICAL INFORMATION

- Biodegradability : Result: Readily biodegradable.  
97 %
- Physico-chemical  
removability : > 70 %  
readily eliminated
- Bioaccumulation : no data available
- Toxicity to fish : LC50  
Species: Leuciscus idus (Golden orfe)  
Dose: 250 - 350 mg/l  
Exposure time: 96 h
- Toxicity to bacteria : EC50  
Species: Bacteria  
Dose: > 5,000 mg/l
- Adsorbed organic bound  
halogens (AOX) : not included
- Volatile organic compounds  
(VOC) content : 5 %
- Additional ecological  
information : Contains no substances known to be hazardous to the  
environment or not degradable in waste water treatment plants.

### SECTION 13. DISPOSAL CONSIDERATIONS

- Adequate disposal : In accordance with local and national regulations.

### SECTION 14. TRANSPORT INFORMATION

**DOT 49 CFR**

## Material Safety Data Sheet

Print Date: 02/16/2006

Revision Date : 02/16/2006

Version : 2.0

Trade name: **Original ATE Brake Fluid TYP 200; 10m (DOT4)**

Not dangerous goods

**TDGR**

Not dangerous goods

**ICAO / IATA-DGR**

Not dangerous goods

**IMDG-Code**

Not dangerous goods

**SECTION 15. REGULATORY INFORMATION**

**TSCA Status** : On TSCA Inventory

**DSL Status** : This product contains the following components listed on the Canadian NDSL list. All other components are on the Canadian DSL list.

2,2'-(Octylimino)bisethanol                      15520-05-5

**California Prop. 65** : This product does not contain any chemicals known to State of California to cause cancer, birth defects or any other reproductive harm.

**WHMIS Classification** : D2B Toxic Material Causing Other Toxic Effects  
 Moderate skin irritant  
 Severe eye irritant

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

**SECTION 16. OTHER INFORMATION**

**Further information**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

## Material Safety Data Sheet

Print Date: 02/16/2006

Revision Date : 02/16/2006

Version : 2.0

Trade name: **Original ATE Brake Fluid TYP 200; 10m (DOT4)**

---

Prepared by : GWU mbH  
Birlenbacher Str. 18  
D-57078 Siegen  
Germany  
Telephone: +49-(0)271-88072-0

Revision Date : 02/16/2006

---