



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/30/2015

Version 6

Reviewed on 05/30/2015

1 Identification

Product identifier

Trade name: Original ATE Brake Fluid DOT 3 G (yellow)

Article number: 03.9901-53xx.x / 7053xx

Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture hydraulic liquid

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Continental Aftermarket GmbH

Guerickestr. 7

60488 Frankfurt a. M.

Germany

Tel: +49-69-76031

Fax: +49-69-761061

Information department:

Gefahrstoffmanagement Konzern, Zentrales Materiallabor

ate.sicherheit@contiautomotive.com

Emergency telephone number: +49-6132-84463

2 Hazard(s) identification

Classification of the substance or mixture



Health hazard

Suspected of damaging fertility or the unborn child.

May cause damage to the kidneys through prolonged or repeated exposure. Route of exposure: Oral.

Label elements

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms GHS08

Signal word Warning

Hazard-determining components of labeling:

2-(2-methoxyethoxy)ethanol

2,2'-oxybisethanol

Hazard statements

Suspected of damaging fertility or the unborn child.

May cause damage to the kidneys through prolonged or repeated exposure. Route of exposure: Oral.

Precautionary statements

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear eye protection / face protection.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

IF exposed or concerned: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

CA



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/30/2015

Version 6

Reviewed on 05/30/2015

Trade name: Original ATE Brake Fluid DOT 3 G (yellow)

(Contd. of page 1)

Classification system:**NFPA ratings (scale 0 - 4)**

Health = 0
Fire = 1
Reactivity = 0

HMS-ratings (scale 0 - 4)

Health = *0
Fire = 1
Reactivity = 0

Other hazards**Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixtures**Description:** Mixture of the substances listed below with nonhazardous additions.**Dangerous components:**

161907-77-3	Ethanol, 2-butoxy-, manufacture of, by-products from Eye Dam. 1, H318	<20%
111-46-6	2,2'-oxybisethanol STOT RE 2, H373; Acute Tox. 4, H302	<10%
111-77-3	2-(2-methoxyethoxy)ethanol Repr. 2, H361; Flam. Liq. 4, H227	<3%

4 First-aid measures

Description of first aid measures**General information:** Remove contaminated clothes and shoes immediately.**After inhalation:** Supply fresh air; consult doctor in case of complaints.**After skin contact:** Immediately wash with water and soap and rinse thoroughly.**After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Call a doctor immediately.**Information for doctor:****Most important symptoms and effects, both acute and delayed**

No further relevant information available.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

Extinguishing media**Suitable extinguishing agents:**CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire fighting measures that suit the environment.

For safety reasons unsuitable extinguishing agents: Water with full jet**Special hazards arising from the substance or mixture**May be released in case of fire: CO, CO₂, NO_x

(Contd. on page 3)



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/30/2015

Version 6

Reviewed on 05/30/2015

Trade name: Original ATE Brake Fluid DOT 3 G (yellow)

(Contd. of page 2)

Advice for firefighters

Protective equipment:

Do not inhale explosion gases or combustion gases.
Wear self-contained respiratory protective device.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation

Environmental precautions:

Do not allow product to reach sewage system or any water course.
Do not allow to penetrate the ground/soil.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of the collected material according to regulations.

Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

Handling:

Precautions for safe handling

Keep out of the reach of children.
Open and handle receptacle with care.
Ensure good ventilation/exhaustion at the workplace.

Information about protection against explosions and fires: No special measures required.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Storage at room temperature.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions:

Store in dry conditions.
This product is hygroscopic.
Keep receptacle tightly sealed.

Storage class: 10 combustible liquids.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical systems: No further data; see item 7.

Control parameters

Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.

Breathing equipment:

If occupational exposure limits are exceeded, use breathing mask (filter type A). Wear self-contained breathing apparatus in case of danger of oxygen displacement.

(Contd. on page 4)



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/30/2015

Version 6

Reviewed on 05/30/2015

Trade name: Original ATE Brake Fluid DOT 3 G (yellow)

(Contd. of page 3)

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material

Butyl caoutchouc (butyl rubber): minimum breakthrough times 180 min; minimum layer thickness: 0.7 mm

NBR (nitrile rubber): minimum breakthrough times 30 min; minimum layer thickness: 0.4 mm

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Safety glasses

Limitation and supervision of exposure into the environment

See section 6 and 7. No additional measures necessary.

9 Physical and chemical properties

Information on basic physical and chemical properties
General Information
Appearance:

Form:	Fluid
Color:	Light yellow
Odor:	Characteristic
Odour threshold:	Not determined.

pH-value at 20 °C: 7.5 - 10 (FMVSS 116)

Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	> 245 °C (FMVSS 116)

Flash point: > 130 °C (ASTM D 7094 (closed cup))

Flammability (solid, gaseous): Not applicable.

Ignition temperature: 230 °C (DIN 51794)

Decomposition temperature: >360 °C (DSC)

Auto igniting: Product is not selfigniting.

Danger of explosion: Product does not present an explosion hazard.

Explosion limits:

Lower:	1.5 Vol %
Upper:	Not determined.

Vapor pressure at 20 °C: < 10 hPa

Density at 20 °C:	1.04 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Water:	Fully miscible.

Partition coefficient (n-octanol/water): Not determined.

Viscosity:

Dynamic:	Not determined.
-----------------	-----------------

(Contd. on page 5)

CA



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/30/2015

Version 6

Reviewed on 05/30/2015

Trade name: Original ATE Brake Fluid DOT 3 G (yellow)

(Contd. of page 4)

Kinematic at 20 °C:	14.5 - 17 mm ² /s (FMVSS 116)
Solvent content:	
Organic solvents:	37.9 %
Water:	0.1 %
Other information	No further relevant information available.

10 Stability and reactivity

Reactivity

Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

Possibility of hazardous reactions No dangerous reactions known.

Conditions to avoid No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

Information on toxicological effects

Acute toxicity:

LD/LC50 values that are relevant for classification:

Oral LD50 >2000 mg/kg (-)

Primary irritant effect:

on the skin: No irritant effect.

on the eye: No irritating effect.

Sensitization: No sensitizing effects known.

Additional toxicological information:

Carcinogenic categories

IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

NTP (National Toxicology Program)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

Toxicity

Aquatic toxicity:

EC50 >15000 mg/l (bacteria)

LL50 596 mg/L (fish) (DIN 38412)

Persistence and degradability No further relevant information available.

Other information: The product is easily biodegradable.

Behavior in environmental systems:

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Additional ecological information:

General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

(Contd. on page 6)



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/30/2015

Version 6

Reviewed on 05/30/2015

Trade name: Original ATE Brake Fluid DOT 3 G (yellow)

(Contd. of page 5)

Do not allow product to reach ground water, water course or sewage system.

Results of PBT and vPvB assessment Not applicable.**PBT:** Not applicable.**vPvB:** Not applicable.**Other adverse effects** No further relevant information available.

13 Disposal considerations

Waste treatment methods

Waste disposal according EC-regulations 75/442/EEC and 91/689/EEC in the corresponding versions, covering waste and dangerous waste.

Recommendation: Must be specially treated adhering to official regulations.
Uncleaned packagings:
Recommendation:

Packagings that cannot be cleansed are to be disposed of in the same manner as the product.

14 Transport information

UN-Number

DOT, TDG, ADN, IMDG, IATA	Void
---------------------------	------

UN proper shipping name

DOT, TDG, ADN, IMDG, IATA	Void
---------------------------	------

Transport hazard class(es)

DOT, TDG, ADN, IMDG, IATA Class	Void
------------------------------------	------

Packing group

DOT, TDG, IMDG, IATA	Void
----------------------	------

Environmental hazards:

Marine pollutant:	No
--------------------------	----

Special precautions for user

Not applicable.

**Transport in bulk according to Annex II of
MARPOL73/78 and the IBC Code**

Not applicable.

UN "Model Regulation":

UN-, -

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture
Sara
Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

143-22-6	2-[2-(2-butoxyethoxy)ethoxy]ethanol
----------	-------------------------------------

111-77-3	2-(2-methoxyethoxy)ethanol
----------	----------------------------

TSCA (Toxic Substances Control Act):

23783-42-8	2-(2-methoxyethoxy)ethanol
------------	----------------------------

112-35-6	2-(2-(2-methoxyethoxy)ethoxy)ethanol
----------	--------------------------------------

161907-77-3	Ethanol, 2-butoxy-, manufacture of, by-products from
-------------	--

(Contd. on page 7)



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/30/2015

Version 6

Reviewed on 05/30/2015

Trade name: Original ATE Brake Fluid DOT 3 G (yellow)

(Contd. of page 6)

112-27-6	2,2'-(ethylenedioxy)diethanol
111-46-6	2,2'-oxybisethanol
112-60-7	3,6,9-trioxaundecane-1,11-diol
111-77-3	2-(2-methoxyethoxy)ethanol
24991-55-7	Polyethylenglykol dimethylether
110-97-4	1,1'-iminodipropan-2-ol
4792-15-8	3,6,9,12-tetraoxatetradecane-1,14-diol
26780-96-1	2, 2, 4-trimethyl-1, 2-dihydroquinoline polymer
29385-43-1	methyl-1H-benzotriazole
4314-14-1	Fat Yellow 3G
68439-46-3	Alcohol ethoxylate (C9-C11, 6 EO)
7732-18-5	water, distilled, conductivity or of similar purity

Proposition 65**Chemicals known to cause cancer:**

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

Carcinogeny categories**EPA (Environmental Protection Agency)**

None of the ingredients is listed.

TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

Canadian substance listings:**Canadian Domestic Substances List (DSL)**

23783-42-8	2-(2-methoxyethoxy)ethanol
112-35-6	2-(2-(2-methoxyethoxy)ethoxy)ethanol
112-27-6	2,2'-(ethylenedioxy)diethanol
111-46-6	2,2'-oxybisethanol
112-60-7	3,6,9-trioxaundecane-1,11-diol
24991-55-7	Polyethylenglykol dimethylether
110-97-4	1,1'-iminodipropan-2-ol
4792-15-8	3,6,9,12-tetraoxatetradecane-1,14-diol
26780-96-1	2, 2, 4-trimethyl-1, 2-dihydroquinoline polymer
29385-43-1	methyl-1H-benzotriazole
4314-14-1	Fat Yellow 3G
68439-46-3	Alcohol ethoxylate (C9-C11, 6 EO)
7732-18-5	water, distilled, conductivity or of similar purity

Canadian Ingredient Disclosure list (limit 0.1%)

None of the ingredients is listed.

Canadian Ingredient Disclosure list (limit 1%)

112-27-6	2,2'-(ethylenedioxy)diethanol
----------	-------------------------------

(Contd. on page 8)



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/30/2015

Version 6

Reviewed on 05/30/2015

Trade name: Original ATE Brake Fluid DOT 3 G (yellow)

(Contd. of page 7)

111-77-3 | 2-(2-methoxyethoxy)ethanol

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Recommended restriction of use For industrial purposes only.

Department issuing MSDS:

Hazardous substances management
 industriehygiene@conti.de

Contact:

Mr. Dr. Vogelpohl
 Phone: +49(0)511-938 59519

Date of preparation / last revision 05/30/2015 / 5

Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 Flam. Liq. 4: Flammable liquids, Hazard Category 4
 Acute Tox. 4: Acute toxicity, Hazard Category 4
 Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1
 Repr. 2: Reproductive toxicity, Hazard Category 2
 STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Sources

* **Data compared to the previous version altered.**

CA